

Specifications

Model		NT554-RE1T	NT554-E1	NT548-E1	NT540-RE1T	NT540-E1	NT536-E1
Dimensions	Overall length (mm)	3,365			3,020		
	Overall width (mm)	1,600		1,570	1,460		
	Overall height (mm)	2,335	1,670	1,640	2,300	1,500	
	Wheel base (mm)	1,980			1,675		
	Min. ground clearance (mm)	400		390	400	390	
	Weight (kg)	1,705	1,660	1,640	1,300	1,260	1,250
Engine	Model	E4DD-DB		E4CG-DB	E3CG-TDB		E3CG-DB
	Output HP (kW) at rpm	54 (39.7) @2,600		48 (35.3) @2,600	40 (29.4) @2,700		36 (26.6) @2,700
	Number of cylinder	4			3		
	Displacement (cc)	2835		2197	1,647		
	Fuel injection	Direct			Direct		
	Fuel tank capacity (L)	52			43		
Transmission	Number of Gear	F8/R8			F8/R8		
	Forward speed (km/h)	1.6 - 26.2		1.57 - 23.37	1.90 - 22.99		1.95 - 22.5
	Main clutch	Dry single			Dry single		
	Shuttle	Synchronized			Synchronized		
PTO	PTO Speed (rpm)	540/750			540/750		
	Lift capacity at link end (kg)	1,420			1,000		
	Auxiliary Valve	○	Opt.	Opt.	Opt.	Opt.	Opt.
Rops	Canopy	○	×	×	○	×	×
	Rear ROPS	○	Opt.	Opt.	○	Opt.	Opt.