

			TXG237F3	
Dimension	Overall length	(mm)	2,580 (with 3-point linkage)	
	Overall width	(mm)	1,220	
	Overall height	(mm)	2,310 (with ROPS and agri tire)	
			2,300 (with ROPS and Turf tire)	
	Wheelbase	(mm)	1,450	
	Tread	Front	(mm)	930
		Rear	(mm)	840
Weight (including ISEKI standard seat)	(kg)	680(with agri tire) 675(with turf tire)		
Engine	Model		E3112	
	Number of cylinder		3	
	Displacement	(L)	1.123	
	Output	Gross (PS)	22.5	
	Rate speed	(min ⁻¹)	2,600	
	Fuel tank capacity	(L)	25	
Transmission	Main change		HST	
	Sub change		2	
	HST pedal		2 Pedals	
PTO	Clutch		Independent	
	Mid PTO		Std.	
		Speed	(min ⁻¹)	2,000
	Rear PTO	Change		1
Speed		(min ⁻¹)	540	
Rear Axle	Diff. lock		Std. (Left Pedal)	
	Brake		Wet disks	
	Brake pedal		1 Pedal (right)	
	Parking brake		Lever	
	Maximum speed (No load @2860rpm)	Forward	(km/h)	15.6 (with agri tire) 15.3 (with turf tire)
		Reverse	(km/h)	10.6 (with agri tire) 10.4 (with turf tire)
Tire	Agri	Front	18X8.50-8	
		Rear	26X12.00-12	
	Turf	Front	18X8.50-8	
		Rear	26X12.00-12	
Front Axle	Type		2WD/4WD	
	Steering		Power steering	
	Front hitch		Factory option (G model : Std.)	
Hydraulic	3-point linkage	At the ball end	(kgf) 540	
		24inch behind	(kgf) 310	
	Pump capacity	(L/min)	24	
	Position control lever		Up & down	
	Aux. valve		Factory option (V model : x2)	
3-point linkage	Category		Category 1	
	Rear hitch		Factory option (G model: Std.)	
Electric	Front light		Std.	
	7 pin socket		Std. (G model)	
	Fuel gauge		Std.	
	Tachometer		Std.	
	Engine water temperature gauge		Std.	
	Combination switch		Column type	
Exterior	Floor		Full flat	
	Floor mat		Std.	
	Rear view mirror		Std. (right & left)	
	Seat		Factory option (Z model: Std.)	
	Beacon lamp switch		Std.	
	Engine hood		Flip up	
ROPS	ROPS		Rear (R: model)	