

## Specification

		SF237	SF225	
Dimension	Overall length (mm)	2,790	2,725	
	Overall width (mm)	1,245		
	Overall height (mm)	2,120		
	Wheelbase (mm)	1,375	1,275	
	Weight (model: BGZRE) (kg)	1,060	910	
Engine	Model	ISEKI		
	Output (PS)	34.9	22.2	
	No. of cylinders	3		
	Displacement (L)	1.826	1.123	
	Rated rotation speed (min-1)	2,600		
	Exhaust gas regulations	StageV		
	Fuel tank capacity	40		
Transmission	Transmission	HST		
	HST pedals	2 pedals		
PTO	Front side (for mower)	Clutch	Wet multiple disk	
		Rate speed (min-1)	2,000 @2,600	
	Front center (for blower)		Std	
		Clutch	Wet multiple disk	
Front axle	Diff. lock		Std (Lh)	
	Brake	Type	Dry drum	
		Position	Lh	
	Parking brake		Lever	
	Max. traveling speed	Forward (km/h)	15.0	
Reverse (km/h)		10.0		
Tire	Turf	Front	23x10.50-12	
		Rear	18x8.5-8	
Rear axle	4WD/2WD		Auto or 4WD	
	Steering		Power steering	
	Tilt steering		Std	
	Aux. valve for mower deck & collector		Std (3 valves)	
Electric	Front light & rear combination lamp		Std (homologated)	
	Meter	Fuel gauge	Std (Electric)	
		Hour meter	Std	
	Warning lamp	Battery charge		Std
		Engine oil pressure		Std
		Engine water temperature		Std (with buzzer)
		Parking brake		Std
		Collector full		Std (with buzzer)
4WD-On		Std		
Exterior	Engine hood		Tilt	
	Seat		Factory opt (Z model: armrest & suspension seat)	
	Floor mat		Std	
	Rear weight		Opt (without blower model is std.)	
ROPS		Std (foldable)		

## Specification

		SCMB60	New	SCMA54	SSM54
Mower	Cutting width (inch)	60"	←	54"	←
	Discharge	Center	←	←	Side
	Number of blade	4	←	2	3
	Flip-up angle	65°	←	←	60°
	Cutting height adjustment	1 action lever	Hydraulic	1 action lever	Pin type
	Min. cutting height (mm)	25	←	←	30

		SBC950F3
Collector	Capacity (L)	950
	Container	Plastic
	Dump	Hydraulic
	Lift	Hydraulic
	Dump height (mm)	2,250(SF237)