Model				SF310	SF370	
Dimensions	Overall length		mm(in.)	2450	2450 (96.5)	
	Overall width		mm(in.)	1230/1330 wide	1230/1330 wide (48.4/52.4 wide)	
	Overall height		mm(in.)	2180/2200 wide	2180/2200 wide (85.8/86.6 wide) *1	
Weight kg(lbs.)			935/945 wide (2061/2083 wide) *2			
			895/905 wide (1975/1997 wide) *3			
Engine	Model			E3CD-VG03	E3CD-VTG	
	Туре			Vertical Water-cooled, 4-cycle Diesel		
	No. of cylinders			3		
	Total displacement		cm3(cu.in)	1498	1498 (91.5)	
	Output (net)		kw(ps)	21.8(30)	26.0(35)	
	Rated revolution		rpm	25	2500	
Generator capacity amp.			60			
Battery			80D26R			
Fuel			Diesel fuel			
Fuel tank capacity liter(gal)			48 (12.7)			
Transmission	Main transmission			HST (hydrostatic transmission)		
	Transmission range			Manual shift, 2 stages		
	Travelling speeds	Forward	km/hr(mph)	22.4/22.8 wide (14.0/14.2 wide)		
		Reverse	km/hr(mph)		e (7.5/7.6 wide)	
Wheel base m			mm(in)	1250 (49.2)		
Wheel tread	Front		mm(in)	1000/1025 wide (39.4/40.4 wide)		
	Rear		mm(in)		960/1010 wide (37.8/39.8 wide)	
Driving system			2/4WD automatic shift - Permanent 4WD			
Steering system	Mechanism			Power		
	Steered wheels			Rear wheels		
Min. un-cut radius mm(ir			mm(in)	1050 (41.3)		
Brake system			Wet,multi-disk			
Min. ground clearance mm(in)			175/200 wide (6.9/7.9 wide)			
Tyre size	Front			23x10.5-12/26x12.0-12wide		
	Rear			20x8.0-10/22x8.50-12wide		
PTO	Location			Front		
	Туре			Wet multi disks		
	Drive			Shaft drive		
	On-Off				Switch	
	Revolution		mm(in)	2050		

<sup>\*1</sup> At the top of ROPS

<sup>\*2</sup> When equipped with wide tire, seat, ROPS and full fuel tank
\*3 When equipped with wide tire, seat, and ROPS, and without full fuel tank
(Specifications and design subject to change without notice)