## **Specifications**

Name			Iseki tiller
Model name			SA150
Class			SE4
Dimensions	Total length	(mm)	1570
	Total width	(mm)	860
	Total height	(mm)	1060
Total weight (kg)		(kg)	62
Engine	Engine model		EX17
	Туре		Air cooled 4-cycle 1 cylinder OHC petrol
	Total displacement	(L)	0.169
	Output (kW{PS}/rpm)		Rated 2.9{3.9}/3600 Max. 4.2{5.7}/4000
	Fuel		Lead-free petrol for vehicles
	Tank capacity	(L)	3.2
	Starting method		Recoil starter
	Air cleaner		Dry (dual element)
	Spark plug		TORCH-E6RC or NGK-BR6HS
Traveling	Clutch type		Belt tension (deadman, unlock button)
	Transmission		Gear - chain
	No. of speeds (step)		Forward 1, Reverse 1
	Rotating speed of rotors (rpm) [Rated engine speed]		Forward 98 Reverse 35
	Diameter of rotor (mm)		320
	Tillage width (mm)		860 , 560
	Side disc		Standard
Resistance bar (step)		(step)	2-stage up and down (fixed with pin)
Transport wheel			Standard (one-touch, front side)
Нэ	Handlebar adjustment angle rotation		Multistage (tooth gear)
i ia			1-stage each to the right and left
Noise (dB)		` '	87±2 (at the operator's ear)
Vibration (m/s <sup>2</sup> )		(m/s <sup>2</sup> )	24±2 (handlebar grip)

<sup>•</sup> The specifications may be changed without notice to improve.