

## 10. Others

### 10.4 Specifications

<b>Name</b>		Iseki tiller
<b>Model name</b>		SA250
<b>Class</b>		SE4
<b>Dimensions</b>	<b>Total length (mm)</b>	1550
	<b>Total width (mm)</b>	860
	<b>Total height (mm)</b>	1060
<b>Total weight (kg)</b>		65
<b>Engine</b>	<b>Engine model</b>	EX17
	<b>Type</b>	Air cooled 4-cycle 1 cylinder OHC petrol
	<b>Total displacement (L)</b>	0.169
	<b>Output (kW{PS}/rpm)</b>	Rated 2.9{3.9}/3600 Max. 4.2{5.7}/4000
	<b>Fuel</b>	Lead-free petrol for vehicles
	<b>Tank capacity (L)</b>	3.2
	<b>Starting method</b>	Recoil starter
	<b>Air cleaner</b>	Dry (dual element)
	<b>Spark plug</b>	TORCH-E6RC or NGK-BR6HS
<b>Traveling</b>	<b>Clutch type</b>	Belt tension (deadman, unlock button)
	<b>Transmission</b>	Gear - chain
	<b>No. of speeds (step)</b>	Forward 4, Reverse 2
	<b>Rotating speed of rotors (rpm) [Rated engine speed]</b>	Forward 26, 39, 66, 100 Reverse 16, 25
	<b>Diameter of rotor (mm)</b>	320
	<b>Tillage width (mm)</b>	860, 560
	<b>Side disc</b>	Standard
<b>Resistance bar (step)</b>		2-stage up and down (fixed with pin)
<b>Transport wheel</b>		Standard (one-touch, front side)
<b>Handlebar adjustment</b>	<b>angle</b>	Multistage (tooth gear)
	<b>rotation</b>	1-stage each to the right and left
<b>Noise (dB)</b>		87±2 (at the operator's ear)
<b>Vibration (m/s<sup>2</sup>)</b>		24±2 (handlebar grip)

● The specifications may be changed without notice to improve.