

## 13. Specifications

		TLE3410	TLE3410H	
		ZVRE4A	ZVRE4	
		Mech	HST	
Dimension	Overall length (mm)	3,075(w3P)	3,075(w3P)	
	Overall width (mm)	1,385	1,490	
	Overall Height (mm)	2,395	2,615	
	Wheel base (mm)	1,675	←	
	Weight (kg)	1,435	1,405	
Engine	Manufacture	ISEKI	←	
	Model	E3FH	←	
	Number of cylinder	3	←	
	Displacement (L)	1.826	←	
	Declared rated net Power (kW), (Regulation (EU) 2016/1628) (PS{KW})	40.0{29.4}	←	
	Rated engine speed (min-1)	2,600	←	
	Max torque	112.5/1600	←	
	Regulation of emission	StageV	←	
	Fuel tank (L)	40	←	
	Transmission	Main clutch	Dry single	-
Transmission Shuttle		Synchro	HST	
Stages		F8/R8	3	
Lever position		Main	Center	-
	Sub	Left	Left	
PTO	Clutch	Independent	←	
	Mid PTO	NA	←	
	Rear PTO	Stages	1	←
		speed (min-1)	540	←
	Stationary PTO	Std.	←	
Rear axle	Diff lock	Pedal (right)	←	
	Brake	Wet disk	←	
	Pedal	2 pedal (right)	←	
	Max. speed	Forward (no load) (km/h)	25.9	26.4
		Rear (km/h)	19.7	19.1

## 13. Specifications

			TLE3410F	TLE3410H
			ZVRE4A	ZVRE4
			Mech	HST
tire	Agri	Forward	7-16	←
		Rear	11.2-24	←
	Turf	Forward	212/80D15	←
		Rear	355/80D20	←
Front axle	4WD/2WD		4WD/2WD	←
	Steering		Power steering	←
	Tilt		NA	←
Hydraulic	Pump capacity (L/min)		28.3	←
	Aux. valve		Std. : x1 Opt. : x2	←
3P	Hydraulic	Edge (kgf)	1,000	←
		24 inch behind (kgf)	810	←
	Position control		Std.	←
	3P Category		Category I	←
	Rear hitch		Clevis drawbar	←
	Beacon lump switch		Std.	←
Exterior	Floor		Semi flat	←
	Floor mat		Std.	←
	Back mirror		Std.	←
	Seat		Std.	←
	Engine hood		1 piece full open	←
ROPS			Center	Rear

## 12. Specification

		TLE4550			
		SZVRE4A	SZVRE4		
		TYTLE4490F1E	TYTLE4490F1E	TYTLE4490F2E	
Dimension	Overall length (mm)	3,450			
	Overall width (mm)	1470/1520/1590	1520/1590	1,690	
	Overall height (mm)	2,385	2,660	2,555	
	Wheel base (mm)	1,980			
	Minimum ground clearance (mm) (Front Axle)	345		240	
	Weight (kg)	1,885	1,750	1,825	
Engine	Manufacture	ISEKI			
	Model	E4FH			
	Number of cylinder	4			
	Displacement (L)	2.434			
	Declared rated n2016/1628) et Power (kW) (Regulation (EU) (PS{kW}))	54.4{40}			
	Rated engine speed (min-1)	2,600			
	Max torque (N·m/min-1)	175 / 1600			
	Regulation of emission	StageV			
	Combustion chamber	Swirl chamber			
	Fuel tank capacity (L)	54			
Transmission	Main clutch	Mech			
	Transmission	Main	4 (Full synchronize)		
		Sub	3		
		F12/R12			
PTO	Clutch	Independent			
	Rear PTO	Number of gear	1		
		Speed (min-1)	540		
	Mid PTO		Option		
		Number of gear	1		
		Speed (min-1)	2,000		
	Shaft diameter (mm)	35			
Rear Axle	Diff-lock	Pedal			
	Brake	Wet disk			
	Brake pedal type	Two pedals			
	Parking brake	Lever			

## 12. Specification

			TLE4550		
			SZVRE4A	SZVRE4	
			TYTLE4490F1E	TYTLE4490F1E	TYTLE4490F2E
Hydraulic	3P lift capacity kgf	@ link end	1,200		
		@ 24" behind	1,100		
	Pump capacity	Main (L/min)	32.2		
	Draft control		Opt.		
	Aux. valve		Std. x1, Opt. x2		
3P	3P linkage	Category	1		
	Rear hitch		Clevis drawbar		
Exterior	Floor type		Full-flat		
	Floor mat		Standard		
	Back mirror		Left & Right		
	Seat		Std. (with "Z" model)		
ROPS	Type		Center	Rear	