

12. Specification

			TM3185F3		
			ZRE4	UZRE4	
			with TY3160F1E	with TY3160F1E	
Dimension	Overall length	(mm)	2,350		
	Overall width	(mm)	1,105		
	Overall height	(mm)	2,255		
	Wheel base	(mm)	1,305		
	Weight (without operator)	(kg)	570	580	
Engine	Model		3TNV70-XKIST		
	Engine output	Gross	(kW {PS})	11.7 {15.9}	
		Net	(kW {PS})	11.5 {15.6}	
	Number of cylinder		3		
	Displacement	(L)	0.854		
	Revolution	(min-1)	2,800		
	Combustion Chamber		Swirl chamber		
Fuel tank capacity	(L)	14			
Transmission	Gear	Main	3		
		Sub	2		
	Number of Gear		F6/R2		
PTO	Mid PTO		NA		
	Rear PTO	Number of Gear	1		
		Speed (min-1)	540		
Rear Axle	Brake		Wet disc		
	Brake Pedal Type		Two pedals		
	Parking Brake		Lever type		
	Diff-lock		Std. (Pedal)		
	Max. Speed	Forward	(km/h)	19.5	
		Reverse	(km/h)	10.7	
Front Axle	Type		4WD, 2WD		
	Steering		Manual steering	Power steering	
	Front Bumper		Opt.		
	Front Hitch		Std.		
Hydraulic	3-point linkage lift capacity	@ link end	(kgf)	540	
		@ 24inch behind	(kgf)	280	
	3-point linkage control		Position Control		
	Aux. Valve		Opt.		
Electric	Power terminal of beacon lamp		Std.		
Exterior	Floor		Semi Flat		
	Floor Mat		Std.		
	Seat		Std.		
	Rear-view mirror		Std..		
ROPS	Rear ROPS		Std.		
	Type		Foldable		
EU Homologation	Homologation Category		(EU) No. 167/2013		

12. Specification

			TM3185F3		
			ZRE4	UZRE4	
			with TY213F2E	with TY213F2E	
Dimension	Overall length	(mm)	2,350		
	Overall width	(mm)	1,105		
	Overall height	(mm)	2,220		
	Wheel base	(mm)	1,305		
	Weight (without operator)	(kg)	570	580	
Engine	Model		3TNV70-XKIST		
	Engine output	Gross	(kW {PS})	11.7 {15.9}	
		Net	(kW {PS})	11.5 {15.6}	
	Number of cylinder		3		
	Displacement	(L)	0.854		
	Revolution	(min-1)	2,800		
	Combustion Chamber		Swirl chamber		
Fuel tank capacity	(L)	14			
Transmission	Gear	Main		3	
		Sub		2	
	Number of Gear		F6/R2		
PTO	Mid PTO		NA		
	Rear PTO	Number of Gear		1	
		Speed (min-1)		540	
Rear Axle	Brake		Wet disc		
	Brake Pedal Type		Two pedals		
	Parking Brake		Lever type		
	Diff-lock		Std. (Pedal)		
	Max. Speed	Forward	(km/h)	17.8	
Reverse		(km/h)	9.7		
Front Axle	Type		4WD, 2WD		
	Steering		Manual steering	Power steering	
	Front Bumper		Opt.		
	Front Hitch		Std.		
Hydraulic	3-point linkage lift capacity	@ link end	(kgf)	540	
		@ 24inch behind	(kgf)	280	
	3-point linkage control		Position Control		
	Aux. Valve		Opt.		
Electric	Power terminal of beacon lamp		Std.		
Exterior	Floor		Semi Flat		
	Floor Mat		Std.		
	Seat		Std.		
	Rear-view mirror		Std..		
ROPS	Rear ROPS		Std.		
	Type		Foldable		
EU Homologation	Homologation Category		(EU) No. 167/2013		