

17. Specification

			TXGS24F	
Dimension	Overall height	with ROPS	(mm)	2,352
		ROPS folded	(mm)	1,610
	Overall width		(mm)	1,220
	Overall length		(mm)	2,580
	Minimum ground clearance		(mm)	165
	Weight		(kg)	690
Engine	Manufacturer			ISEKI
	Model			E3112
	Output		(PS)	22.5
	Rate rotation		(min1)	2,600
	Number of cylinder			3
	Displacement		(cc)	1,123
	Fuel tank capacity		(L)	25
	Emission regulation			StageV
Transmission	Main			HST
	Sub			2
	Brake			Left or right
	Cruise control			Standard
PTO	Control			Control lever
	Rear		(rpm)	540
		Independent		
Mid		(rpm)	2,000	
Hydraulics	Maximum pump	Main	(L/min)	24
	3P category			Category 1
	3P Lift capacity		(kg)	540
	3P Lift capacity after 24 inch		(kg)	310
	Joystick			Standard (J model)
	Aux. valve x3			Standard (V model)
Tire	Industrial	Front		18X8.50-10
		Rear		26X12.00-12
	Agri	Front		18X8.50-10
		Rear		26X12.00-12
	Turf	Front		18X8.50-10
		Rear		26X12.00-12
Other	Seat			Standard (Z model)
	Tilt steering			Standard
	12V electric socket			Standard
	ROPS			Foldable with damper
Axle load capacity	Front	(kg)		650
	Rear	(kg)		960
	Total	(kg)		1,420

17. Specification

Mower deck

Model	SSM60 TXGS24E4	SSM54 TXGS24E4	SMM54 TXGS24E4	SRM54 TXGS24E4
Discharge	Side (right)	Side (right)	Mulching	Rear
Color	Black	Black	Black	Black
Applicable model	TXGS24	TXGS24	TXGS24	TXGS24
	TXG237	TXG237	TXG237	TXG237
Driving method	Universal joint	Universal joint	Universal joint	Universal joint
Blade	3	3	6*	3
Cutting stage	x7	x7	x7	x7
Cutting height (mm)	25-115	25-115	25-115	25-115
Dimension	Overall length (mm)	995	929	983
	Overall width (mm)	1,893	1,708	1,449
	Overall height (mm)	331	331	331
	Cutting width (mm)	1,524	1,369	1,369
	Weight (kg)	130	110	110
Lift height (mm)	150	150	150	150
Lift type	3P	3P	3P	3P
Lift cylinder	Opt	Opt	Opt	Opt
Gauge wheel (front)	Std	Std	Std	Std
Gauge wheel (rear)	Std	Std	Std	Std
Over mount	Available	Available	Available	Available
Universal joint	Quick attach	Quick attach	Quick attach	Quick attach

*Local arrangement

17. Specification

Mower deck

Model		SSM48 TXG23E4F	SRM48 TXG23E4F
Discharge		Side (right)	Rear
Color		Black	Black
Applicable model		TXGS24	TXGS24
		TXG237	TXG237
Driving method		Universal joint	Universal joint
Blade		3	3
Cutting stage		x7	x7
Cutting height (mm)		30-120	30-120
Dimension	Overall length (mm)	862	842
	Overall width (mm)	1,523	1,272
	Overall height (mm)	274	274
	Cutting width (mm)	1,224	1,225
	Weight (kg)	70	77
Lift height (mm)		150	150
Lift type		3P	3P
Lift cylinder		Opt	Opt
Gauge wheel (front)		Std	Std
Gauge wheel (rear)		Std	Std
Over mount		-	-
Universal joint		-	-

*Local arrangement